

## ACKNOWLEDGEMENT

The organizing committee would like to acknowledge the following for their contribution and effort to this conference:



اَبُو سَيِّدِي تَيْكُو لُو كِي مَارَا  
UNIVERSITI  
TEKNOLOGI  
MARA

F|S|P|U

Fakulti Senibina, Perancangan & Ukur  
*Faculty of Architecture, Planning & Surveying*

**IOP** Conference Series  
Earth and Environmental Science



## Preface

The 3rd International Conference on Research Methodology in Built Environment and Engineering (ICRMBEE 2017), held on 8<sup>th</sup> to 9<sup>th</sup> November 2017 at Best Western Hotel I-City, Shah Alam, Malaysia. This year mark the 3<sup>rd</sup> instalments of ICRMBEE series that carries the same focus on the method adopted in the area of built environment and engineering. With the theme, *'Regenerative Sustainability in Built Environment for Human Livability'*, ICRMBEE 2017 hope to provides an opportunity for interaction and exchange of ideas on the most appropriate ways of building bridges across universities, research institutions, government, industry and experts from around the world in signifying built environment and engineering research in the societal livelihood. We are proud to announce that all accepted papers will be published in the IOP Conference Series: Earth and Environmental Science indexed in SCOPUS.

Research and innovation has helped the globalization, modernization and the development of human capital in many ways. This year ICRMBEE is trying to connect human liveability into the equations, not just the quantitative and qualitative means of research methodology. We hope to see many research methods are carved and contour with regards to benefit our nations livability that add up to a community's quality of life, including the built and natural environments, economic prosperity, social stability and equity, educational opportunity, and cultural, entertainment and recreation possibilities. The organizing committee of ICRMBEE 2017 aims to make the conference grows into a renowned avenue and platform for global intellectual discourse.

*Sr Dr Siti Aekbal Salleh*  
Conference Chair ICRMBEE 2017  
Faculty of Architecture Planning and Surrveying  
Universiti Teknologi MARA  
40450 Shah Alam, Selangor  
Malaysia



**Organizing Committees**

Profesor Datin Sr Dr Hamimah Adnan  
Sr Dr. Siti Aekbal Salleh  
TPr Dr. Marlyana Azyyati Marzukhi  
Farrah Norizzah Mohd Yussof  
Noor Aisyah Asyikin Mahat  
Har Einur Azrin Baharuddin  
Dr Norazian Mohamad Yusuwan  
Dr Rumaizah Mohd Nordin  
Dr Ani Saifuza Abd Shukor  
Dr Norfashiha Hashim  
Sr. Masnizan Che Mat  
Dr Zaharah Yahya  
Sharifah Nur Aina Syed Alwee  
Dr. Shamsida Saidan Khaderi  
Dr. Salina Mohamed Ali  
Rafiuddin Roslan  
Mohd Ridzwan Mohd Yusoff  
Mohd Arif Marhani  
Dr Rostam Yaman  
Hanyzam Selamat  
Norishahaini Mohamed Ishak  
Ahmad Arzlee Hassan  
Abdul Ízz Mohamad Kamil  
Muhammad Bahtiar Masidin  
Nurulhuda Abdul Hamid @ Yusoff  
Norajlin Jaini  
Nurul Afida Isnaini Janipha  
Hazwani Ramli  
Sufia Hafizah Mohd Zuki  
Nurul Fazlina Mohamad Nooh

**Guest Editors:**

Sr. Dr. Siti Aekbal Salleh  
Dr. Norazian Mohamad Yusuwan



# ANFIS multi criteria decision making for overseas construction projects: a methodology

W P Utama<sup>1\*2</sup>, A P C Chan<sup>2</sup>, Zulherman<sup>3</sup>, H Zahoor<sup>3</sup>, R Gao<sup>1</sup>  
and D Y Jumas<sup>2</sup>

<sup>1</sup> Department of Building and Real Estate, The Hong Kong Polytechnic University

<sup>2</sup> Department of Quantity Surveying, Universitas Bung Hatta, Indonesia.

<sup>3</sup> Department of Construction Engineering and Management, National University of Science and Technology, Risalpur Campus, Pakistan.

\*wahyudi.utama@connect.polyu.hk

**Abstract.** A critical part when a company targeting a foreign market is how to make a better decision in connection with potential project selection. Since different attributes of information are often incomplete, imprecise and ill-defined in overseas projects selection, the process of decision making by relying on the experiences and intuition is a risky attitude. This paper aims to demonstrate a decision support method in deciding overseas construction projects (OCPs). An Adaptive Neuro-Fuzzy Inference System (ANFIS), the amalgamation of Neural Network and Fuzzy Theory, was used as decision support tool to decide to *go* or *not go* on OCPs. Root mean square error (RMSE) and coefficient of correlation (R) were employed to identify the ANFIS system indicating an optimum and efficient result. The optimum result was obtained from ANFIS network with two input membership functions, Gaussian membership function (*gaussmf*) and hybrid optimization method. The result shows that ANFIS may help the decision-making process for go/not go decision in OCPs.

## 1. Introduction

In the topic of internationalization of construction enterprises, the application of Multi-criteria Decision Making (MCDM) methods can be addressed to assess the capability of enterprises to operate outside their market origin and evaluate the potential projects to be considered for go or for bid [1]. In such decision, intuition and experience of decision makers in judging the capability of the firm may be more dominant. Several approaches such as Analytical Hierarchy Process [2], Cross Impact Analysis [3] and Analytical Network Process [4] have been adopted to solve the decision making problems in OCPs. Indeed, the intuition of decision makers plays important role in strategic decision making [5].

This study aims to demonstrate the integration of neuro-fuzzy system to support management decision in choosing OCPs. Adaptive Neuro-Fuzzy Inference System (ANFIS), a type of amalgamation of neural network (NN) and fuzzy logic (FL), was utilized to develop the decision model. NN can be used for dealing with a given problem if a set of data sample are available. Learning and computational abilities are the power of the NN [6]. Hence, a mathematical formulation and the previous knowledges are not necessary. The problem is that the solution deriving from the learning process in the networks cannot be interpreted because the character of the neural network seems a black box. On the other hand, the FL can be adopted to settle the problem if there is knowledge about the solution and the system can



be created by using the linguistic *if-then* rules. This system does not need training data and a mathematical model of the problem of interest [7]. The integration of the two systems will bring advantages to existing ones.

## 2. Concept of ANFIS

The basic concept of ANFIS is to create the stipulated input-output pairs through assembling a set of fuzzy if-then rules with suitable membership functions through implanting the Fuzzy Inference Rule (FIS) into the structure of adaptive networks [8]. The ANFIS model structure is constructed by both ANN and fuzzy logic which allow the model to work with uncertain and imprecise information [9]. It utilizes the NN training process to tune the membership function (MF) and the related parameter approaching the desired data sets [10]. Structurally, ANFIS consists of three devices namely, a rule base, a database, and a reasoning mechanism. The rule base constitutes fuzzy if-then rules following a linear function as described by Takagi and Sugeno [11].

Rule 1: IF  $X_1$  is  $A_1$  and  $X_2$  is  $A_1$  THEN  $Y_1 = p_1x_1 + q_1x_2 + r_1$

Rule 2: IF  $X_1$  is  $A_2$  and  $X_2$  is  $A_2$  THEN  $Y_2 = p_2x_1 + q_2x_2 + r_2$

Where  $X_1$ ,  $X_2$  and  $Y_1$  and  $Y_2$  are numerical inputs and outputs respectively,  $A$  and  $B$  are numerical variables, and  $p$ ,  $q$  and  $r$  are the parameters determining the relation between input and output. ANFIS algorithm is composed of five layers as follows:

*Layer 1:* This layer shows the number of numerical inputs belonging to different fuzzy sets. Every node  $i$  in this layer is represented by square node with the output function as shown in Equation 1.

$$\begin{cases} \mu_i(x) \\ \mu_i(x) \end{cases} \quad (1)$$

Where  $\mu_i(x)$  and  $\mu_i(x)$  are membership functions of  $A$  and  $B$  fuzzy sets.

*Layer 2:* In this layer, all incoming signals are multiplied to obtain an output,  $\omega$  by which operator AND or OR are used, known as firing strength. The output is calculated by Equation 2.

$$\omega_i = \mu_i(x) \times \mu_i(x) \quad (2)$$

*Layer 3:* Every node  $N$  in this layer calculates the average ratio of previous outputs to produce a new output  $\bar{\omega}$ . It is obtained by Equation 3.

$$\bar{\omega} = \frac{\omega_i}{\sum \omega} \quad (3)$$

*Layer 4:* Square node in this layer produces an output  $\bar{\omega}f_i$  based on Equation 4.

$$Y_i = \bar{\omega}f_i = \bar{\omega}(p_i x + q_i x + r_i) \quad (4)$$


*Layer 5:* This is an output layer in which the node calculates all outputs from Layer 4 by Equation 5.

$$Y = \sum \bar{\omega}f_i = \frac{\sum \omega f_i}{\sum \omega} \quad (5)$$

Learning process in a neural network aims to create a stable structure. In ANFIS, the learning process of network combines the least square estimate (LSE) and the gradient descent method. This hybrid learning procedure is composed of a forward step in which the input signal passes forward until Layer 4, where the output parameters are adjusted using the LSE of the error between the estimated output and the actual output. Then, on the backward step, the error rates propagate back through the system, and MFs in Layer 1 are updated by the gradient descent method [12]. The process of these forward and backward propagations is called as epoch. The hybrid learning algorithm trains the MF parameters to mimic the training data set.

## 3. Methodology

The hierarchy structure of the model development for OCP selection is illustrated in Figure 1. It consists of four main steps; determination of attributes, data collection, ANFIS operation, and recommendation. The process begins with a determination of criteria for OCP assessment. These criteria were obtained from data analysis of Delphi survey. Based on the criteria, an evaluation form of OCP was designed as an instrument to build cases database.



**Figure 1.** Hierarchical structure of model development

Two methods, convergence and generalization proposed by Refenes [13] were adapted to validate and verify the applicability and performance of the model. Convergence views the learning mechanism implemented for training data. It indicates the optimum performance of the model and the accuracy. The indicator to measure the performance is Root Mean Square Error (RMSE). Regarding its efficiency, the model is indicated by the correlation coefficient (R) formulated as:

$$R = \frac{\sum_{i=1}^N (A_i - \bar{A})(F_i - \bar{F})}{\sqrt{\sum_{i=1}^N (A_i - \bar{A})^2 \times \sum_{i=1}^N (F_i - \bar{F})^2}} \quad (6)$$

Where  $A_i$ ,  $F_i$  and  $N$  are actual scores, calculated score produced by model and number of data respectively. The ideal characteristics of the model have RMSE score of 0 and R closed to 1 or 100%.

#### 4. ANFIS based ‘Go/Not go’ decision model

ANFIS system needs a set of input-output pair data. In preparation of such data, the OCP cases were then tabulated in a table presenting five input attributes (project, contract, owner, host country and business) and one output (Go/Not Go). The grades given by the experts were then normalized using equation  $x' = \frac{x - \min}{\max - \min}$  where  $x'$  is normalized score,  $x$  is initial score, and  $\min$  and  $\max$  are the smallest and the largest scores. This equation casts the initial scores in one unified range [0 to 1]. The different ranges between input value and output value need the data to be normalized.

On the output side, the categorical scales on decision (Y) should be transformed into crisp number in which the program can recognize the input attribute. Linguistic variables of output were coded in a binary digit representing 1 for Go and 0 for Not Go. However, Lam et al. [14] advice that the use of 1 and 0 approach in imitative based learning algorithms result in very slow learning speed. They suggest assigning 0.95 and 0.05 instead of 1 and 0 to avoid expected slow convergence. The cases are then divided into training (70%), testing (20%) and checking (10%) data sets. The training data set is used for generating an initial ANFIS model, whereas the testing and checking data sets are used for validation and generalization of the model respectively.

Before starting the fuzzy inference system (FIS) training, an initial FIS model structure needs to be specified by choosing *grid partition* that generates a single-output Sugeno-type FIS by using grid partitioning on the data. While generating FIS, the number of membership functions (MFs) at INPUT, were set for [2 2 2 2 2] which indicate that each input has two MFs (Low – High), whereas their type of MFs were set at “trimf” indicating triangular MF, and at OUTPUT, “linear” was chosen as the type of MF. The ANFIS editor provides eight types of MFs. This setting creates an ANFIS model structure in which to obtain the optimum ANFIS model indicated by the training minimum error, the number and type of input MFs are tuned arbitrarily.

Given the above parameters, the system was trained with *hybrid* learning algorithm. Another set parameter in ANFIS editor is *Error tolerance*, which determines a stopping criterion of training related to the size of error. The training error is the variance between the output value of training data set and



the output of the FIS for the same input value of training data set. The training error records RMSE of the training and checking data sets at each epoch.


Each Train-FIS process basically creates an ANFIS model which is a trained system. As stated above, the average training error records the RMSE, and to find the RMSE of each data set, the trained systems were then tested against training, testing and checking data set. Test-FIS in ANFIS editor is used to test the data set. The average train errors shown for each option constitute the RMSE for the given data as tabulated in Table 1.

**Table 1.** Result of Test-FIS of training, testing and checking data

No	Type of MF	Average training error (RMSE)					
		2 MFs of input			3 MFs of input		
		Train	Test	Check	Train	Test	Check
1	Trimf	$1.14 \times 10^{-5}$	0.304	0.215	$2.97 \times 10^{-7}$	0.277	0.295
2	Trapmf	$6.52 \times 10^{-6}$	0.256	0.148	$1.44 \times 10^{-7}$	0.227	0.323
3	Gbellmf	$5.71 \times 10^{-6}$	0.347	0.153	$3.17 \times 10^{-7}$	0.119	0.160
4	Gaussmf	$5.31 \times 10^{-6}$	0.130	0.075	$1.90 \times 10^{-7}$	0.220	0.287
5	Gauss2mf	$7.89 \times 10^{-6}$	0.305	0.172	$1.33 \times 10^{-7}$	0.203	0.396
6	Pimf	$5.82 \times 10^{-6}$	0.290	0.139	$1.23 \times 10^{-7}$	0.208	0.405
7	Psigmf	$4.30 \times 10^{-6}$	0.277	0.109	$1.66 \times 10^{-7}$	0.196	0.370
8	Dsignmf	$4.30 \times 10^{-6}$	0.277	0.109	$1.66 \times 10^{-7}$	0.196	0.370

Overall, the RMSE of each data for various numbers and types of MFs show very small value (close to zero). Generally, these values can be said that the network works well under all parameters. The minimum training errors of training data for two and three number MFs of input were obtained from *gaussmf* ( $5.31 \times 10^{-6}$ ) and *trapmf* ( $1.44 \times 10^{-7}$ ) respectively. The average training errors for testing the data of both parameters were 0.130 and 0.227, and for checking the data were 0.075 and 0.323. Based on the results, the ANFIS model for GO/Not Go decision on OCP was developed using three parameters: two input membership functions, Gaussian membership function (*gaussmf*), and hybrid optimization method.

Of the trained system, the ANFIS rule which is the ANFIS model for GO/Not GO decision making in OCP was obtained as illustrated in Figure 2. This IF-THEN rule displays the all records of FIS and enables management to make a quick choice of OCP by substituting the input scores based on an analysis of a particular project. Changes made on score of each input generate a new output value. Thus, the decision makers can further determine a threshold output score in deciding Go or Not Go for OCPs under evaluation.



**Figure 2.** ANFIS rule of Go/Not go decision model



The correlation coefficient (R) between testing/checking data output and output result of trained ANFIS signifies the efficiency of the model. To calculate R value, first, the desired and predicted outputs were collected. Using ANFIS rule (Figure 2), the input scores of 22 testing and 11 checking data were set, while the generated outputs were then recorded. The score of R for testing and checking data set was then calculated using the given equation. The results are 0.995 and 0.976 showing a strong correlation and an indication of the fitness of the designed ANFIS model. Of both RMSE and R, values can be summarized that the performance of designed ANFIS model for Go/Not Go decision making in OCPs was found to be satisfactory.

The generalization ability of the ANFIS model is then examined further. Nine real cases of OCPs performed by Indonesian firms were used for this purpose. Before assessing the decision of the projects using ANFIS model for Go/Not Go decision making, the input data was normalized. Each normalized project data was then entered into trained system in which the ANFIS rule (Figure 2) processes the data and generates an output score. With nine real-life cases of OCPs executed by Indonesian large contractors, the ANFIS model could predict the desirable decision with 11.11% fault. The result of real cases suggests a very good generalization ability of the proposed ANFIS model for Go/Not go decision making in OCPs.

## 5. Conclusion

This paper demonstrates the ability of ANFIS for supporting the decision-making in OCPs selection. The developed model using this approach gives several advantages combining fuzzy reasoning (e.g. ability in handling uncertainty regarding imperfect information) and neural network (i.e. ability in learning and generalizing from a set of prior knowledges). The developed model was based on the simulation cases of OCPs which evaluates the Indonesian contractors. The evaluation results may be different from other contractors, so the model may also diver.

The use of simulation cases and small number of data sets are the limitation of this study. However, there exist several advantages of using simulation cases, such as a freedom to select attributes contributing to the complexity of the structure of data, and the possibility of tuning different scenarios tailored to meet various conditions which are not available in real data sets. In future, the use of an appropriate numbers of real data sets is encouraged. A cross-validation method, comparing results with other approaches, such as statistical techniques and case based reasoning, can be carried out to view the accuracy of each tool.

## References

- [1] Utama, W.P., Chan, A.P.C., Gao, R. and Zahoor, H. (2017). 'Making international expansion decision for construction enterprises with multiple criteria: a literature review approach', *International Journal of Construction Management*, doi: 10.1080/15623599.2017.1315527.
- [2] Hastak, M. and Shaked, A. (2000). 'ICRAM-1: Model for International Construction Risk Assessment', *Journal of Management in Engineering*, Vol. 16 (1), pp. 59-69.
- [3] Han, S.H., Diekmann, J.E. and Ock, J.H. (2005). 'Contractor's risk attitudes in the selection of international construction projects', *Journal of Construction Engineering and Management*, Vol. 131 (3), pp. 283-292.
- [4] Bu-Qammaz, A.S., Dikmen, I. and Birgonul, M.T. (2009). 'Risk assessment of international construction projects using the analytic network process', *Canadian Journal of Civil Engineering*, Vol. 36 (7), pp. 1170-1181.
- [5] Khatri, N. and Ng, H.A. (2000). 'The role of intuition in strategic decision making', *Human relations*, Vol. 53 (1), pp. 57-86.
- [6] Canuto, A. M. D. P. (2001). *Combining neural networks and fuzzy logic for applications in character recognition*. Doctoral dissertation, University of Kent at Canterbury.

- [7] Nauck, D., Klawonn, F. and Kruse, R. (1997). *Foundation of neural neuro-fuzzy systems*. Sussex, UK: John Wiley & Sons Ltd.
- [8] Jang, J.S. (1993). 'ANFIS: adaptive-network-based fuzzy inference system', *IEEE transactions on systems, man, and cybernetics*, Vol. 23 (3), pp. 665-685.
- [9] Liu, M. and Ling, F. Y. Y. (2003). Using fuzzy neural network approach to estimate contractors' markup. *Building and Environment*, 38(11), 1303-1308.
- [10] Wu, J. D., Hsu, C. C. and Chen, H. C. (2009). An expert system of price forecasting for used cars using adaptive neuro-fuzzy inference. *Expert Systems with Applications*, 36(4), 7809-7817.
- [11] Takagi, T. and Sugeno, M. (1985). 'Fuzzy identification of system and its application to modelling and control', *IEEE Transactions on systems, man and cybernetics*, Vol. 15, pp. 116-132.
- [12] Opeyemi, O. and Justice, E.O. (2012). 'Development of neuro-fuzzy system for early prediction of heart attack', *International Journal of Information Technology and Computer Science (IJITCS)*, Vol. 4 (9), p. 22.
- [13] Refenes, A.N. (1995). *Neural network design considerations*. In Refenes, A. N. (ed). *Neural Networks in the capital markets*. pp. 67-76, John Wiley, NY.
- [14] Lam, K., Hu, T., Thomas Ng, S., Skitmore, M. and Cheung, S. (2001). 'A fuzzy neural network approach for contractor prequalification', *Construction Management & Economics*, Vol. 19 (2), pp.175-188.



UNIVERSITI  
TEKNOLOGI  
MARA

F|S|P|U  
Fakulti SeniBina, Perancangan & Ukur  
Faculty of Architecture, Planning & Surveying

"GENERATIONS OF  
PROFESSIONAL  
EXCELLENCE"



## ICRMBEE 2017

3<sup>RD</sup> INTERNATIONAL CONFERENCE ON RESEARCH METHODOLOGY  
FOR BUILT ENVIRONMENT AND ENGINEERING

# Certificate of Participation

This certificate of participation is hereby granted to

**W.P. Utama, Albert P.C. Chan, Zulherman, H. Zahoor, R. Gao, D.Y. Jumas**

for their paper entitled

**ANFIS Multi Criteria Decision Making For Overseas  
Construction Projects: A Methodology**

presented in the

**3rd INTERNATIONAL CONFERENCE ON RESEARCH  
METHODOLOGY FOR BUILT ENVIRONMENT AND ENGINEERING  
(ICRMBEE 2017)**

organised by

**RESEARCH MANAGEMENT UNIT (RMU)  
FACULTY ARCHITECTURE, PLANNING AND SURVEYING  
UiTM SHAH ALAM**

on  
**8-9 NOVEMBER 2017**

**DEAN**

Faculty Architecture, Planning and Surveying  
UiTM, 40450 Shah Alam, Selangor  
[www.fspu.uitm.edu.my](http://www.fspu.uitm.edu.my)